

P 4


| | |
|----|-----|
| 1 | N.C |
| 2 | N.C |
| 3 | VSS |
| 4 | VSS |
| 5 | N.C |
| 6 | N.C |
| 7 | TXD |
| 8 | TXD |
| 9 | N.C |
| 10 | N.C |
| 11 | RXD |
| 12 | RXD |
| 13 | N.C |
| 14 | N.C |
| 15 | VDD |
| 16 | VDD |
| 17 | N.C |
| 18 | N.C |

P1

| PIN NO. | SIGNAL |
|---------|--------|
| 1 | KEY1 |
| 2 | KEY2 |

P2,P3

| PIN NO. | SIGNAL | PIN NO. | SIGNAL | PIN NO. | SIGNAL |
|---------|--------|---------|--------|---------|--------|
| 1 | VSS | 7 | BUSY | 13 | DB2 |
| 2 | VDD | 8 | DB7 | 14 | DB1 |
| 3 | REQ | 9 | DB6 | 15 | DB0 |
| 4 | RST | 10 | DB5 | | |
| 5 | TXD | 11 | DB4 | | |
| 6 | RXD | 12 | DB3 | | |



NOTE

- 1 DISPLAY TYPE : FSTN
- 2 VIEWING DIRECTION: 6 O' CLOCK
- 3 POLARIZER MODE : TRANSFLECTIVE/POSITIVE
- 4 DRIVE METHOD : 1/128DUTY 1/11BIAS
- 5 OPERATING VOLTAGE: 13.0V
- 6 LOGIC VOLTAGE : 3.0 V
- 7 CONTROLLOER IC : ST5668A
- 8 工作温度范围 : 零下40度到+70度。
- 9 存储温度范围 : 零下40度到+75度。
- 10 BACK LIGHT : LED

北京中显电子有限公司

WWW.ZXLCD.COM

010-82626833

MODEL NO. : ZX128128M1A-D40

UNIT: MM SCALE: 1:1

DESIGNED BY:

DEFAULT TOERANCE: ±0.2

CHECKED BY:

NO. : 1 OF: 1

APPROVED BY:

DATE:

