



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
VSS	VDD	V0	RS	R/W	E	D0	D1	D2	D3	D4	D5	D6	D7	A	K

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW -GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: $-10^{\circ}\text{C} \text{---} +60^{\circ}\text{C}$
- 5.STORAGE TEMP: $-20^{\circ}\text{C} \text{---} +70^{\circ}\text{C}$
- 6.LCD OPERATING VOLTAGE: 18.5V
- 7.DRIVE METHOD: 1/64DUTY 1/9BIAS
- 8.CONTROLLER: KS0108BX2
- 9.BACKLIGHT: LED<YELLOW -GREEN;4.2DCV>
- 10.ALL UNMARKED TOLERANCES: $\pm 0.3\text{mm}$
- 11.BEZEL<THICKNESS:0.6mm> IS TO BE PAINTED BLACK

北京中显电子有限公司, www.zxlcd.com					
绘图:		型号:	ZX1601A	单位:	mm
审核:		版号:	08V01	电话:	52926620
批准:		日期:		传真:	52926621