



|     |     |      |    |     |   |     |     |     |     |     |     |     |     |    |    |
|-----|-----|------|----|-----|---|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 1   | 2   | 3    | 4  | 5   | 6 | 7   | 8   | 9   | 10  | 11  | 12  | 13  | 14  | 15 | 16 |
| VSS | VDD | VLCD | RS | R/W | E | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | A  | K  |

NOTES:

- 1.DISPLAY TYPE: STN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C---+60°C
- 5.STORAGE TEMP: -20°C---+70°C
- 6.LCD OPERATING VOLTAGE:-----
- 7.DRIVE METHOD: 1/16DUTY 1/5BIAS
- 8.CONTROLLER: KS0066U
- 9.BACKLIGHT: LED
- 10.ALL UNMARKED TOLERANCES: ±0.3
- 11.BEZEL<THICKNESS:0.6mm> IS TO BE PAINTED BLACK

|                           |  |     |               |     |          |
|---------------------------|--|-----|---------------|-----|----------|
| 北京中显电子有限公司, www.zxlcd.com |  |     |               |     |          |
| 绘图:                       |  | 型号: | ZX1602ADYEYWD | 单位: | mm       |
| 审核:                       |  | 版号: | 08V01         | 电话: | 52926620 |
| 批准:                       |  | 日期: |               | 传真: | 52926621 |