



1	FG	18	FS
2	VSS	19	A
3	VDD	20	K
4	V□	21	VOUT
5	/WR	22	NC
6	/RD	23	ED
7	/CE	24	CDATA
8	C/D	25	FR
9	RESET	26	LP
10	DB0	27	HSCP
11	DB1	28	NC
12	DB2	29	VDD
13	DB3	30	VSS
14	DB4	31	V□
15	DB5	32	VOUT
16	DB6	33	A
17	DB7	34	K

**NOTES:**

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C--+60°C
- 5.STORAGE TEMP: -20°C--+70°C
- 6.VDD: +5.0V
- 7.LCD OPERATING VOLTAGE: 18.5V
- 8.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 9.DRIVE: T6963C
- 10.BACKLIGHT TYPE: LED(YELLOW-GREEN; 5.0±0.1DCV)
- 11.ALL UNMARKED TOLERANCES: ±0.30mm

北京中显电子有限公司, www.zxlcd.com					
绘图:		型号:	ZX240128A-2DYEYWD	单位:	mm
审核:		版本号:	08V01	电话:	52926620
批准:		日期:		传真:	52926621