



1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
VSS	VDD	V0	C/D	RD	WR	D0	D1	D2	D3	D4	D5	D6	D7	CE	RST	VDUT	FS	EL1	EL2

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW -GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C--+70°C
- 5.STORAGE TEMP: -30°C--+80°C
- 6.LCD OPERATING VOLTAGE:16.5V
- 7.DRIVE METHOD: 1/128DUTY 1/12BIAS
- 8.CONTROLLER: T6963C
- 9.BACKLIGHT: LED<YELLOW -GREEN;4.2DCV>
- 10.ALL UNMARKED TOLERANCES:±0.3mm
- 11.BEZEL<THICKNESS:0.6mm> IS TO BE PAINTED BLACK

北京中显电子有限公司, www.zxlcd.com			
绘图:	型号:	ZX240128CDYEYWD	单位: mm
审核:	版本号:	08V01	电话: 52926620
批准:	日期:		传真: 52926621