



1	FG	11	DB1
2	VSS	12	DB2
3	VDD	13	DB3
4	V□	14	DB4
5	/WR	15	DB5
6	/RD	16	DB6
7	/CE	17	DB7
8	C/D	18	FS
9	RESET	19	A
10	DB0	20	K
		21	VOUT

- NOTES:**
- 1.DISPLAY TYPE: STN/YELLOW-GREEN
  - 2.VIEWING DIRECTION: 6:00
  - 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
  - 4.OPERATING TEMP: -10°C--+60°C
  - 5.STORAGE TEMP: -20°C--+70°C
  - 6.VDD: +18.5V
  - 7.DRIVE METHOD: 1/128DUTY 1/12BIAS
  - 8.DRIVE: T6963C
  - 9.BACKLIGHT TYPE: LED(YELLOW-GREEN; 4.2DCV)
  - 10.ALL UNMARKED TOLERANCES: ±0.30mm
  - 11.BEZEL(THICKNESS: 0.6mm)IS TO BE PATNTED BLACK

北京中显电子有限公司, www.zxlcd.com			
绘图:	型号:	ZX240128KDYEYWD	单位: mm
审核:	版号:	08V01	电话: 52926620
批准:	日期:		传真: 52926621