



CON2

1	FLM	8	D3
2	M	9	D4
3	CL1	10	VDD
4	CL2	11	VSS
5	DISPOFF	12	VO
6	D1	13	VEE
7	D2	14	GND

CON1

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
VSS	VDD	VO	/WR	/RD	/CS	A0	/RES	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	A	VOUT

NOTES:

- 1.DISPLAY TYPE: STN Y-G
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C---+70°C
- 5.STORAGE TEMP: -30°C---+80°C
- 6.LCD OPERATING VOLTAGE:-----
- 7.DRIVE METHOD: 1/240DUTY 1/16.27BIAS
- 8.CONTROLLER: SED1335
- 9.BACKLIGHT: CCF/LED
- 10.ALL UNMARKED TOLERANCES:±0.3mm
- 11.BEZEL<THICKNESS:0.6mm> IS TO BE PAINTED BLACK

北京中显电子有限公司, www.zxlcd.com			
绘图:	型号:	ZX320240CDYEYWD	单位: mm
审核:	版号:	08V01	电话: 52926620
批准:	日期:		传真: 52926621