



CON1

1	FRAME	11	D2
2	LOAD	12	D3
3	CP	13	DISPOFF
4	M	14	NC
5	VO	15	NC
6	VDD	16	NC
7	VSS	17	NC
8	VEE	18	VOUT
9	DO	19	NC
10	D1	20	NC

CON2

1	2	3	4	5
VFL1	NC	NC	NC	VFL2

NOTES:

- 1.DISPLAY TYPE: STN/BLUE
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSMISSIVE/NEGATIVE
- 4.OPERATING TEMP: 0C--+50°C
- 5.STORAGE TEMP: -10C--+60°C
- 6.VDD: +5V
- 7.DRIVE METHOD: 1/240DUTY 1/17BIAS
- 8.CONTROLLER: WITHOUT
- 9.BACKLIGHT: CCFL(WHITE)
- 10.ALL UNMARKED TOLERANCES: 0.3mm

LED背光款无此CN2接口，在连接器19脚加+5V,20脚接地即可点亮背光。

北京中显电子有限公司, www.zxlcd.com				
绘图:	型号:	ZX320240BDYEYWD	单位:	mm
审核:	版本号:	08V01	电话:	52926620
批准:	日期:		传真:	52926621