



| | | | | | | | | | | | | | | | |
|-----|-----|------|----|-----|---|-----|-----|-----|-----|-----|-----|-----|-----|----|----|
| 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 |
| GND | VDD | VLCD | RS | R/W | E | DB0 | DB1 | DB2 | DB3 | DB4 | DB5 | DB6 | DB7 | A | K |

NOTES:

- 1.DISPLAY TYPE: STN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE: TRANSPARENTIVE/POSITIVE
- 4.OPERATING TEMP: -10°C---+60°C
- 5.STORAGE TEMP: -20°C---+70°C
- 6.LCD OPERATING VOLTAGE:-----
- 7.DRIVE METHOD: 1/16DUTY 1/5BIAS
- 8.CONTRDOLLER: KS0066U
- 9.BACKLIGHT: LED
- 10.ALL UNMARKED TOLERANCES:±0.3mm
- 11.BEZEL THICKNESS:0.6mm IS TO BE PAINTED BLACK

| | | | |
|---------------------------|-------------------|--------|----------|
| 北京中显电子有限公司, www.zxlcd.com | | 单位: mm | |
| 绘图: | 型号: ZX1602KDYEWWD | 电话: | 52926620 |
| 审核: | 版本号: 08V01 | 传真: | 52926621 |
| 批准: | 日期: | | |

