



P1, P2

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	VSS	7	BUSY	13	DB2
2	VDD	8	DB7	14	DB1
3	REQ	9	DB6	15	DB0
4	RST	10	DB5	16	KEY2
5	TXD	11	DB4	17	KEY1
6	RXD	12	DB3	18(P2)	N.C

P3

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	N.C	7	TXD	13	N.C
2	N.C	8	TXD	14	N.C
3	VSS	9	N.C	15	VDD
4	VSS	10	N.C	16	VDD
5	N.C	11	RXD	17	N.C
6	N.C	12	RXD	18	N.C

- NOTE
- 1 DISPLAY TYPE : STN
 - 2 VIEWING DIRECTION: 12 O' CLOCK
 - 3 POLARIZER : TRANSMISSIVE
 - 4 DRIVE METHOD : 1/65DUTY 1/9BIAS
 - 5 OPERATING VOLTAGE: 9.5V (FOR REFERENCE VOLTAGE)
 - 6 LOGIC VOLTAGE : 2.7~3.6V
 - 7 CONTROLLER : ST5668A
 - 8 OPERATING TEMP : -20° C----+70° C
 - 9 STORAGE TEMP : -30° C----+80° C
 - 10 BACK LIGHT : LED

北京中显电子有限公司		TEL:010-82626833 FAX:51601226	
MODEL NO. : ZX12864M2A		UNIT: MM	SCALE: 1:1
DESIGNED BY: 陶涛		DEFAULT TOERANCE: ±0.2	
CHECKED BY:		NO. : 1 OF: 1	
APPROVED BY:		DATE:	