



P1,P2

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	KEY1	7	RST	13	DB5
2	KEY2	8	TXD	14	DB4
3	PSB	9	RXD	15	DB3
4	VSS	10	BUSY	16	DB2
5	+3V	11	DB7	17	DB1
6	REQ	12	DB6	18	DB0

P3

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	N.C	7	TXD	13	N.C
2	N.C	8	TXD	14	N.C
3	VSS	9	N.C	15	VDD
4	VSS	10	N.C	16	VDD
5	N.C	11	RXD	17	N.C
6	N.C	12	RXD	18	N.C

**NOTE**

- 1 DISPLAY TYPE : FSTN
- 2 VIEWING DIRECTION: 6 O' CLOCK
- 3 POLARIZER MODE : TRANSFLECTIVE/POSITIVE
- 4 DRIVE METHOD : 1/128DUTY 1/12BIAS
- 5 OPERATING VOLTAGE: 16.0V
- 6 LOGIC VOLTAGE : 3.0 V
- 7 CONTROLLER : ST5668A
- 8 OPERATING TEMP : -20° C----70° C
- 9 STORAGE TEMP : -30° C----80° C
- 10 BACK LIGHT : LED/WHITE

**北京中显电子有限公司 TEL : 010-82626833 FAX : 51601226**

MODEL NO. : <b>ZX240128M3A</b>	UNIT: MM SCALE: 1:1
DESIGNED BY:	DEFAULT TOERANCE: ±0.2
CHECKED BY:	NO. : 1 OF: 1
APPROVED BY:	DATE:

