



NOTES:

1. DISPLAY TYPE:
2. OPERATING VOLTAGE:
3. OPERATING TEMPERATURE:
4. STORAGE TEMPERATURE:
5. DRIVE MODE:
6. VIEWING DIRECTION:
7. BACK POLARIZER :

PIN	1	2	3	4	5	6	7	8	9	10
COM	COM	1E	1D	1C	2E	2D	2C	DOT1	3E	3D
PIN	11	12	13	14	15	16	17	18	19	20
COM	3C	DOT2	4E	4D	4C	S6	S5	S4	S3	S2
PIN	21	22	23	24	25	26	27	28	29	30
COM	S1	4B	4A	4F	4G	3B	3A	3F	3G	COL
PIN	31	32	33	34	35	36	37	38		
COM	2B	2A	2F	2G	1B	1A	1F	1G		

北京中显电子有限公司 010-82626833

- TN
- 4.5V
- 20°C~70°C
- 30°C~80°C
- 1/1D,1/1B
- 6:00
- TRANSFLCTIVE, POSITIVE

DESIGNED BY:	VERSION:	VERSION:
CHECKED BY:	1091	NO. 1 OF 1
APPROVED BY:		UNIT: MM
CONFIRMED BY:		DATE: 2005-07-07