


SCALE 1:1



(1-33)PIN FUNCTION AS(34-66)PIN FUNCTION THE SAME

| NO. | SYMBOL | NO. | SYMBOL |
|-----|--------|-----|--------|
| 1 | VDD | 34 | VDD |
| 2 | CLS | 35 | CLS |
| 3 | M/S | 36 | M/S |
| 4 | V0 | 37 | V0 |
| 5 | V1 | 38 | V1 |
| 6 | V2 | 39 | V2 |
| 7 | V3 | 40 | V3 |
| 8 | V4 | 41 | V4 |
| 9 | CAPEN | 42 | CAPEN |
| 10 | CAPEN | 43 | CAPEN |
| 11 | CAPEN | 44 | CAPEN |
| 12 | CAPEN | 45 | CAPEN |
| 13 | CAPEN | 46 | CAPEN |
| 14 | CAPEN | 47 | CAPEN |
| 15 | RES | 48 | RES |
| 16 | RES | 49 | RES |
| 17 | RES | 50 | RES |
| 18 | RES | 51 | RES |
| 19 | RES | 52 | RES |
| 20 | RES | 53 | RES |
| 21 | RES | 54 | RES |
| 22 | RES | 55 | RES |
| 23 | RES | 56 | RES |
| 24 | RES | 57 | RES |
| 25 | RES | 58 | RES |
| 26 | RES | 59 | RES |
| 27 | RES | 60 | RES |
| 28 | RES | 61 | RES |
| 29 | RES | 62 | RES |
| 30 | RES | 63 | RES |
| 31 | RES | 64 | RES |
| 32 | RES | 65 | RES |
| 33 | RES | 66 | RES |



- NOTE:
- 1 DISPLAY TYPE : FSTN
 - 2 VIEWING DIRECTION : 6 O'CLOCK
 - 3 POLARIZER MODE : TRANSMISSIVE/NEGATIVE
 - 4 DRIVE METHOD : 1/64 DUTY 1/9 BIAS
 - 5 OPERATING VOLTAGE : 10.3V(FOR REFERENCE VOLTAGE)
 - 6 OPERATING TEMP : -20°C--+70°C
 - 7 STORAGE TEMP : -30°C--+80°C
 - 8 CONNECTION : COG
 - 9 FRAME FREQUENCY : 64Hz

| REVISION RECORD | | NAME | DATE | | | | | | |
|-----------------|--|------|------|----------|---|---------|----|---------|------------|
| 1 | | | | VERSION | A | UNIT | MM | NO. 1/8 | WY24064-01 |
| 2 | | | | APPROVED | | CHECKED | | DRAWN | |
| 3 | | | | | | | | | |
| 4 | | | | | | | | | |