



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
COM4				COM4	1F	1A	2F	2A	3F	3A	4F	4A	P1	P8	P10	T1	T3	K3							
COM3			COM3		1G	1B	2G	2B	3G	3B	4G	4B	P2	P7	P9		T2	K2	T4						
COM2		COM2			1E	1C	2E	2C	3E	3C	4E	4C	P3	P6				K1	T5						
COM1					1D		2D		3D		4D		P4	P5				COL							

NOTES:

1. DISPLAY TYPE: TN,GRAY
2. POLARIZER TYPE: TRANSMISSIVE,POSITIVE
3. VIEW DIRECTION: 6 O'CLOCK
4. OPERATING TEMPERATURE: 0°C~+50°C
5. STORAGE TEMPERATURE: -10°C~+60°C
6. VDD: +5.0V
7. DRIVE METHOD: 1/4DUTY,1/3BIAS
8. CONTROLLER: HT1621
9. BACKLIGHT TYPE: WHITE
10. BACKLIGHT SUPPLY VOLTAGE: +5.0V

北京中显电子有限公司 010-82626833

DESIGN: MODEL NUMBER: UNITS: MM

CHECK: VERSION: A

APPROVE: SHEET: 1 OF 1

Unspecified tolerances are ±0.3 DATE: 2006-06-17