

4. OUTLINE DIMENSIONS

客户参考图

PH. ASSOCIATION

1	1.50
2	1.50
3	1.50
4	1.50
5	1.50
6	1.50
7	1.50
8	1.50
9	1.50
10	1.50
11	1.50
12	1.50
13	1.50
14	1.50
15	1.50
16	1.50
17	1.50
18	1.50
19	1.50
20	1.50
21	1.50
22	1.50
23	1.50
24	1.50
25	1.50
26	1.50
27	1.50
28	1.50
29	1.50
30	1.50
31	1.50
32	1.50
33	1.50
34	1.50
35	1.50
36	1.50
37	1.50
38	1.50
39	1.50
40	1.50
41	1.50
42	1.50
43	1.50
44	1.50
45	1.50
46	1.50
47	1.50
48	1.50
49	1.50
50	1.50

NOTE:  
1. GENERAL TOLERANCE: ±0.2  
2. CA IS REFERENCE DIMENSION.  
3. DIMENSIONS IN PARENTHESIS INDICATE DIMENSIONS OF OPTIONAL FEATURES.  
4. UNIT: MM (INCH)

Display Type: TFT  
Panel Type: INTRAL WHITE  
Transmittance: TRANSPARENT  
Viewing Angle: 9 O'clock  
Response Time: 10ms  
Operating Temperature: -20°C TO 60°C  
Storage Temperature: -30°C TO 70°C  
Interface Color: WHITE  
Resolution: 1024 X 600  
Refresh Rate: 60Hz  
Viewing Distance: 1000mm

DATE: 2014.08.15

DESIGNER: [Name]

DATE: 2014.08.15

PROJECT NO. S95163

DATE: 2014.08.15

REVISION: 1 OF 1

北京中显电子有限公司