



CONNECTOR PINOUT			
PIN#	SYMBOL	LEVEL	FUNCTIONS
1	FLM	H/L	FRAME PULSE
2	M	H/L	ALTERNATE SIGNAL FOR LCD DRIVE
3	LP	H/L	LATCH PULSE
4	XSCL	H/L	X-DRIVER DATA SHIFT CLOCK
5	YDIS	H/L	POWER-DOWN SIGNAL WHEN DISPLAY IS BLANKED
6	XD0	H/L	X-DRIVER DATA 0
7	XD1	H/L	X-DRIVER DATA 1
8	XD2	H/L	X-DRIVER DATA 2
9	XD3	H/L	X-DRIVER DATA 3
10	Vdd	5V	POWER SUPPLY FOR LOGIC
11	GND	0V	POWER SUPPLY (0V GND)
12	Vee	-18V	NEGATIVE VOLTAGE I/O & LED(K)
13	V0	-15~-18V	CONTRAST ADJUST VOLTAGE
14	GND	0V	POWER SUPPLY (0V GND)

- NOTES:
1. ALL DIMENSIONS IN mm.
 2. LCD TYPE: STN(GRAY)/POSITIVE
 3. VIEWING DIRECTION: 6:00
 4. POLARIZER: TRANSFLECTIVE
 5. DRIVE METHOD: 1/160DUTY; 1/13.6BIAS
 6. OPERATING VOLTAGE: 21.0V
 7. OPERATING TEMPERATURE: -10°C TO +60°C.
 8. STORAGE TEMPERATURE: -20°C TO +70°C.
 9. CONNECTOR: ZEBRA&HEATSEAL
 10. BACKLIGHT: 2 SIDE BACKLIGHT (Y-G)

北京中显电子有限公司, www.zxled.com

绘图:	型号:	ZX240160ADYEYWD	单位:	mm
审核:	版号:	08V01	电话:	52926620
批准:	日期:		传真:	52926621