



P1,P2

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	KEY1	8	RST	15	DB4
2	KEY2	9	TXD	16	DB3
3	PSB	10	RXD	17	DB2
4	TEST	11	BUSY	18	DB1
5	VSS	12	DB7	19	DB0
6	+3V	13	DB6		
7	REQ	14	DB5		

P3

PIN NO.	SIGNAL	PIN NO.	SIGNAL	PIN NO.	SIGNAL
1	NC	7	TXD	13	NC
2	NC	8	TXD	14	NC
3	VSS	9	NC	15	VDD
4	VSS	10	NC	16	VDD
5	NC	11	RXD	17	NC
6	NC	12	RXD	18	NC

NOTE

- 1 DISPLAY TYPE : STN
- 2 VIEWING DIRECTION: 12 O'CLOCK
- 3 POLARIZER MODE : TRANSMISSIVE
- 4 DRIVE METHOD : 1/65DUTY 1/9BIAS
- 5 OPERATING VOLTAGE: 9.5V (FOR REFERENCEVOLTAGE)
- 6 LOGIC VOLTAGE : 2.7~3.6V
- 7 CONTROLLER : ST5668A
- 8 OPERATING TEMP : -20° C---70° C
- 9 STORAGE TEMP : -30° C---+80° C
- 10 BACK LIGHT : LED

北京中显电子有限公司 TEL:010-82626833 FAX:51601226

MODEL NO. : ZX12864M1A

UNIT: MM SCALE: 1:1

DESIGNED BY: 陶陶

DEFAULT TOERANCE: ±0.2

CHECKED BY:

NO. : 1 OF: 1

APPROVED BY:

DATE:

