



1	VSS
2	VDD
3	V0
4	RS (CS)
5	W/R (SID)
6	E (CLK)
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	PSB
16	NC
17	RST
18	NC
19	LED(+)
20	LED(-)

NOTES:

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP:  $-20^{\circ}\text{C} \sim +60^{\circ}\text{C}$
- 5.STORAGE TEMP:  $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/64DUTY 1/9BIAS
- 8.CDNTRROLLER: ST7920
- 9.BACKLIGHT TYPE: LED (YELLOW-GREEN;5.0V)
- 10.ALL UNMARKED TOLERANCES:  $\pm 0.30\text{mm}$

北京中显电子有限公司, <a href="http://www.zxlcd.com">www.zxlcd.com</a>					
绘图:		型号:	ZX12864CR字库	单位:	mm
审核:		版本号:	08V01	电话:	52926620
批准:		日期:		传真:	52926621