


1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
FG	VSS	VDD	NC	R/W	E1	E2	RS	NC	/RST	DB0	DB1	DB2	DB3	DB4	DB5	DB6	DB7	NC	NC



**NOTES:**

- 1.DISPLAY TYPE: STN/YELLOW-GREEN
- 2.VIEWING DIRECTION: 6:00
- 3.POLARIZER MODE:TRANSFLECTIVE/POSITIVE
- 4.OPERATING TEMP: -20°C--+70°C
- 5.STORAGE TEMP: -30°C--+80°C
- 6.VDD: +5.0V
- 7.DRIVE METHOD: 1/32DUTY 1/6.7BIAS
- 8.DRIVE: ST7920X2
- 9.BACKLIGHT TYPE: LED(YELLOW-GREEN; 4.5±0.1DCV)
- 10.ALL UNMARKED TOLERANCES: ±0.30mm
- 11.BEZEL(THICKNESS:0.6mm) IS TO BE PAINTED BLACK

北京中显电子有限公司, www.zxlcd.com			
绘图:	型号:	ZX25664ADYEYWD	单位: mm
审核:	版本号:	08V01	电话: 52926620
批准:	日期:		传真: 52926621