



Pin	Symbol
1	N.C. (NSD)
2	V <sub>SS</sub>
3	V <sub>SS</sub>
4	N.C.
5	V <sub>DD</sub>
6	V <sub>DD</sub>
7	RST
8	CS#
9	RES#
10	DC#
11	R <sub>SW</sub>
12	RES#
13	D2
14	D2
15	D2
16	D2
17	D4
18	D5
19	D5
20	D5
21	RES#
22	VCC#
23	VCC
24	N.C. (NSD)

- Notes:
1. Color: Yellow
  2. Driver IC: SSD1305
  3. FPC Number: UT-0205-F05
  4. Interface: 8-bit 68XX/80XX Parallel, 4-wire SPI, P C
  5. General Tolerance: ±0.30
  6. The total thickness (2.10 Max) is without polarizer protective film & remove tape. The actual assembled total thickness with above materials should be 2.35 Max.

Customer Approval <i>Signature</i>		Univision Technology Inc. UG-2864ASYCG01 Folding Type OEL Display Module Pixel Number: 128 x 64, Monochrome, COG Package				Drawing Number		Rev.	
						DMX2864CNGF29		A	
Unless Otherwise Specified Unit: mm General Roughness: $\sqrt{Ra}$ Tolerance: ±0.3 Angle: ±1		Title	Drawn	E.E.	Panel / E.	P.M.	Material Soda Lime / Polyimide		
		By	Humphrey Lin	James Wang	Ivy Lo	Sean Lin	Scale	Sheet	Size
		Date	20070920	20070920	20070920	20070920	1:1	1 of 1	A3

Item	Date	Remark
A	20070920	Original Drawing